




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : <b>H01J 61/82</b>		<b>A1</b>	(11) International Publication Number: <b>WO 00/45419</b>
			(43) International Publication Date: 3 August 2000 (03.08.00)
(21) International Application Number: PCT/EP00/00216 (22) International Filing Date: 10 January 2000 (10.01.00) (30) Priority Data: 99200253.5          28 January 1999 (28.01.99)          EP (71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). (72) Inventors: KEIJSER, Robertus, A., J.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). ETMAN, Johannes, G. W.; Prof. Holstlaan 6, NL-5656 AA Eindhov Eindhoven (NL). HERREMANS, Hannelore, M., L., E; Prof. Holstlaan 6, NL-5656 AA Eindhov Eindhoven (NL). (74) Agent: DUSSELDORP, Jan, C.; Internationaal Octrooibureau B.V., Prof Holstlaan 6, NL-5656 AA Eindhoven (NL).		(81) Designated States: CN, JP, KR, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>With international search report.</i>	

(54) Title: METAL HALIDE LAMP

## (57) Abstract

The invention relates to a metal halide lamp intended to be operated on an electronic ballast, comprising a discharge vessel (3) having a ceramic wall enclosing a discharge space (11) which contains an ionizable filling comprising, in addition to Hg, a quantity of Na halide, two electrodes (4, 5) with tips (4b, 5b) being arranged at mutual distance EA, the discharge vessel having an internal diameter Di at least through the distance EA such that the following relation is satisfied:  $EA/Di \geq 2.5$  while the lampe has a nominal lampe voltage V<sub>la</sub> of  $\geq 110$  V.



BEST AVAILABLE COPY

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

Metal halide lamp.

The invention relates to a metal halide lamp intended to be operated on an electronic ballast, which lamp comprises a discharge vessel having a ceramic wall enclosing a discharge space which contains an ionizable filling comprising, in addition to Hg, a quantity of Na halide, two electrodes with tips being arranged at a mutual distance EA, and the discharge vessel having an internal diameter Di at least through the distance EA.

A lamp of the type described in the opening paragraph is known from WO 97/42650. The known lamp, which has eminent color properties (inter alia, general color rendering index  $R_a \geq 80$  and a color temperature  $T_c$  of 3000 K), is integrated with the electronic ballast in the form of a switched-mode power supply (smmps) and is thus very suitable as a light source for, inter alia, interior lighting. This lamp is based on the recognition that a good color rendition is possible when Na halide is used as a filling constituent of a lamp and a strong widening and reversal of the Na emission in the Na-D lines occurs during lamp operation. This requires a high temperature of, for example, 1170 K (900°C) of the coldest spot  $T_{kp}$  in the discharge vessel. When reversing and widening the Na-D lines, these take the shape of an emission band in the spectrum with two maxima at a mutual distance  $\Delta\lambda$ .

The requirement for a high value of  $T_{kp}$  results in a relatively small discharge vessel, which, in the practical lamp, leads to a wall load of 70 W/cm<sup>2</sup> measured across the internal surface area of the cylindrical part of the discharge vessel through the distance EA. The required high temperature precludes the use of quartz or quartz glass for the wall of the discharge vessel and necessitates the use of ceramic material for the wall of the discharge vessel.

The ceramic wall in this description and claims is understood to mean both a wall of metal oxide such as, for example, sapphire or densely sintered polycrystalline Al<sub>2</sub>O<sub>3</sub>, or metal nitride, for example AlN.

The electronic ballast comprises a high-frequency converter which converts, as smmps, the low-frequency power supply of the mains into a high-frequency current through the lamp. In this case, it should be ensured that the high frequency is chosen to be such that it does

not give rise to acoustic resonance phenomena in the lamp. Another, generally used configuration as an smps for high-pressure discharge lamps consists of a concatenation of rectifier means, a preconditioner, a converter and a commutator to which the lamp is connected. The preconditioner is used for generating a DC voltage for power supply of the converter while withdrawing a current which is sinusoidal in a satisfactory approximation from the mains operating as the power supply source. The commutator provides for an, often low-frequency, AC current through the lamp. Both forms of the electronic ballast are designed in such a way that the voltage across the lamp is approximately 90 V in the nominal operating condition of the connected lamp. It is thereby achieved that the relevant electronic ballast is suitable for operating known lamps which are generally designed for operation at a lamp voltage of approximately 90 V and can be operated on a ballast in the form of a ballast coil.

In addition to Na, the filling of the discharge vessel may comprise Tl and/or one of the rare earth metals, with which a desired value for the general color rendering index  $R_a \geq 80$  and the color temperature  $T_c$  between 2700 K and more than 4200 K is realized. In this description and claims, the elements Y and the lanthanides are considered as rare earth metals. Due to the formation of compounds with  $O_2$  in ceramic discharge vessels based on metal oxide, Sc is not suitable as a filling constituent.

A drawback of the known lamp is that it has a relatively low specific light output. A further drawback of the known lamp is that, also as a result of the relatively small dimensions of the discharge vessel, a relatively rapid blackening of the wall of the discharge vessel occurs, inter alia, due to deposition of evaporated material on the wall of the electrodes, so that the lumen maintenance and hence the practical lifetime of the lamp is influenced very detrimentally.

It is an object of the invention to provide a measure to combat the described drawbacks while maintaining the satisfactory color properties of the lamp. According to the invention, a lamp as described in the opening paragraph is therefore characterized in that the relation  $EA/D_i \geq 2$  is satisfied, and in that, during nominal operation of the lamp, a lamp voltage  $V_{la}$  satisfying the relation  $V_{la} \geq 110$  V is present across the lamp.

In the lamp according to the invention, it has surprisingly been found that a specific light output above 100 lm/W in combination with a value for the general color rendition  $R_a > 80$  can be realized. The lamp voltage  $V_{la}$  is preferably at most 400 V. Higher

voltages do not lead to a significant improvement of the properties of the lamp but require special efforts for realizing a suitable electronic ballast.

A relatively large electrode distance EA provides the possibility of applying a relatively low wall load, which is favorable for the lifetime of the lamp. During nominal  
5 operation, the lamp according to the invention preferably has a wall load  $W_{la}$  which satisfies the relation  $30 \leq W_{la} < 70$  in  $W/cm^2$ .

In a preferred embodiment of the lamp according to the invention, the discharge vessel also comprises Ce halide. This has the important advantage that a further increase of the specific light output (efficacy) is obtained while maintaining the satisfactory color properties  
10 of the light generated by the lamp. In addition to Na, the filling of the discharge vessel may comprise one or more other metals which form halides, inter alia, for influencing the color properties of the lamp, such as Tl, Dy, Ho and Tm, for example, for raising the color temperature. Moreover, an addition of Ca halide is also suitable.

It holds for Hg that, as is customary for metal halide, it is completely in the  
15 vapor phase in its operational state and constitutes the most important lamp voltage-determining value. It has also been found that Hg influences the color rendition. Notably for realizing values for the general color rendition  $R_a > 80$ , a sufficiently high pressure of the Hg appears to be necessary. To prevent a too high lamp voltage  $V_{la}$ , on the one hand, and an insufficiently high pressure of the Hg, on the other hand, the ratio  $EA/D_i$  is preferably  $\leq 5.5$ .

20 These and other aspects of the invention are apparent from and will be elucidated with reference to the embodiment(s) described hereinafter.

In the drawing:

25 Fig. 1 shows a lamp according to the invention,

Fig. 2 is a cross-section of a discharge vessel of the lamp shown in Fig. 1, and

Fig. 3 shows the lamp of Fig. 1, connected to an electronic ballast.

Fig. 1 shows a metal halide lamp comprising a discharge vessel 3 shown in a cross-section and not to scale in Fig. 2 and having a ceramic wall enclosing a discharge space  
30 11 which contains an ionizable filling in the lamp shown of not only Hg and a quantity of Na halides but also Tl and Dy and Ce halides. Two electrodes 4, 5 with electrode bars 4a, 5a and tips 4b, 5b are arranged in the discharge space at a mutual distance EA, in the drawing each of W. The discharge vessel has an internal diameter  $D_i$  at least through the distance EA. The discharge vessel is sealed at one side by a ceramic projecting plug 34, 35 which tightly

encloses a current feedthrough conductor 40, 41 and 50, 51 with an interspace to the electrodes 4, 5 arranged in the discharge vessel and is connected thereto in a gastight manner by means of a melt-ceramic compound 10 near one end remote from the discharge space. The discharge vessel is enclosed by an outer envelope 1 provided at one end with a lamp cap 2. In the  
5 operational state of the lamp, a discharge extends between the electrodes 4, 5. Electrode 4 is connected via a current conductor 8 to a first electric contact which forms part of the lamp cap 2. Electrode 5 is connected via a current conductor 9 to a second electric contact which forms part of the lamp cap 2. The metal halide lamp shown is intended to be operated on an electronic ballast as is shown in Fig. 3. The lamp indicated by L in Fig. 3 is connected by  
10 means of electric contacts of lamp cap 2 to connection points C, D of a commutator III, for example, a bridge circuit. A, B denote input terminals of the ballast and are intended for connection to a power supply source, for example, a mains of 220 V, 50 Hz. In the ballast, I denotes rectifier means and a preconditioner for generating a DC voltage for power supply of a converter II. Very suitable as a preconditioner is, for example, an up-converter or boost  
15 converter for withdrawing a current, which is sinusoidal in a good approximation, from the mains operating as the power supply source. A suitable example of a converter is a down-converter or a Buck converter. Another type of circuit which is usable as a converter II is a flyback converter. During nominal operation of the lamp shown, a lamp voltage  $V_{la}$  satisfying the relation  $V_{la} \geq 110$  V is present across the lamp. The lamp voltage is measurable between  
20 the electric contacts which form part of the lamp cap 2 and, in a good approximation, corresponds to the voltage between the electrode tips 4b, 5b.

In a first, practical embodiment of lamps according to the invention and as shown in the drawings, the nominal power of the lamp is 39 W. The translucent wall of the discharge vessel has a thickness of 0.8 mm. The ionizable filling of the lamp comprises, in  
25 addition to Hg, 5.5 mg of Na+Tl+Dy+Ce iodide with a composition of 85.3; 3.6; 4.8 and 6.3 in mol%. Moreover, the discharge vessel comprises Ar as a starter with a filling pressure of 400 mbar. Table I states further data and results. For lamp Prototype 1 the Hg filling amount is 2.1 mg and for lamp Prototype 2 it is 2.5 mg.

Table I

Pro tot ype	Hg $\mu\text{g}/\text{mm}^3$	Di( mm)	EA (m m)	EA/Di	$V_{la}$ (V)	$\Delta\lambda$ (nm)	Efficacy (lm/W)	Ra	$T_c$ (K)	$T_{kp}$ (K)	$W_{bel}$ (W/c $\text{m}^2$ )
1	30	3	8	2.67	150	7.5	107	88	2940	1300	51
2	25.5	3	12	4	200	5.3	115	82	2930	1280	35

In a second practical embodiment of lamps according to the invention, the nominal power of the lamps is 75 W. Table II states the data and results of these lamps.

5

Table II

Pro to Ty pe	Hg $\mu\text{g}/\text{mm}^3$	Di (m m)	EA (mm)	EA/ Di	$V_{la}$ (V)	$\Delta\lambda$ (n m)	Efficacy (lm/W)	Ra	$T_c$ (K)	$T_{kp}$ (K)	$W_{bel}$ (W/ $\text{cm}^2$ )
1	24.5	4	12	3	205	4.3	118	87	2940	1330	50
2	24	4	15	3.75	245	3.2	117	85	2960	1295	40
3	25	4	9	2.25	175	5.3	110	91	2950	1345	66

In a further practical embodiment of a lamp according to the invention, the filling of the discharge vessel comprises 5.75 mg of Na, Tl, Dy, Ce iodide in a weight ratio of 64.3; 6.0; 13.1 and 16.5. The nominal power of the lamp is 75 W. The electrode distance EA is 12 mm, the internal diameter is 4 mm which corresponds to a wall load  $W_{bel}$  of 49.7 W/cm<sup>2</sup> in the operational state. During operation, a Hg pressure of 35 bar prevails in the discharge vessel

SUBSTITUTE SHEET (RULE 26)

and the lamp voltage  $V_{la}$  is 232 V. The lamp having a specific light output value of 109 lm/W emits light at a color temperature  $T_c$  of 2800 K with a value of 90 for the general color rendering index  $R_a$ .

For a comparable lamp, the values of EA and Di are 9 mm and 4.5 mm, respectively, the Hg pressure during operation is 43 bar and the lamp voltage  $V_{la}$  is 202 V. The specific light output values,  $T_c$  and  $R_a$  of this lamp are 106 lm/W, 3050 K and 93, respectively. In this case, the wall load  $W_{la}$  is 59 W/cm<sup>2</sup>. For a lamp with a discharge vessel of the same construction, the Hg pressure during operation is 31 bar. The lamp operated in a vertical position has a lamp voltage of 147 V, a specific light output of 115 lm/W, a color temperature  $T_c$  of 3670 K of the emitted light and an  $R_a$  value of 82.


In a further practical embodiment of the lamp according to the invention, the nominal power of the lamp is 39 W. The electrode distance EA is 8 mm, the internal diameter Di is 3 mm. In addition to Hg with a pressure of 31 bar in the operational state, the filling of the discharge vessel comprises 5.7 mg of Na, Ca, Ce, Dy - iodides in a mol% of 47; 39.2; 7.7; 6.1. For a 100-hour lifetime of the lamp, lamp properties were measured with the following results: lamp voltage  $V_{la}$  174 V; specific light output 106 lm/W; color temperature  $T_c$  3965 K; general color rendering index  $R_a$  89. After a lifetime of 1000 hours, these measured values were 178 V; 101 lm/W; 3801 K; 87, respectively.

A further practical lamp of a corresponding construction and nominal power is provided with 1 mg of Hg and 5.6 mg of Na, Ca, Ce, Dy iodide in a mol% of 45.2; 37.7; 11.2; 5.9. The lamp voltage for lifetimes of 100 hours and 1000 hours was 150 V and 153 V, respectively. The value of the specific light output was 106 lm/W and 102 lm/W, respectively. The associated values for the color temperature  $T_c$  and the general color rendering index  $R_a$  were 4648 K and 84, and 4569 K and 84, respectively.



## CLAIMS

1. A metal halide lamp intended to be operated on an electronic ballast, which lamp comprises a discharge vessel having a ceramic wall enclosing a discharge space which contains an ionizable filling comprising, in addition to Hg, a quantity of Na halide, two electrodes with tips being arranged at a mutual distance EA, and the discharge vessel having  
5 an internal diameter Di at least through the distance EA, characterized in that the relation  $EA/Di \geq 2$  is satisfied and in that, during nominal operation of the lamp, a lamp voltage V<sub>la</sub> satisfying the relation  $V_{la} \geq 110 \text{ V}$  is present across the lamp.
2. A lamp as claimed in claim 1, characterized in that the lamp voltage V<sub>la</sub> is at  
10 most 400 V.
3. A lamp as claimed in claim 1 or 2, characterized in that, during nominal operation, it has a wall load W<sub>la</sub> which satisfies the relation  $30 \leq W_{la} < 70$  in W/cm<sup>2</sup>.
- 15 4. A lamp as claimed in claim 1, 2 or 3, characterized in that the ratio EA/Di is preferably  $\leq 5.5$ .
5. A lamp as claimed in claim 1, 2, 3 or 4, characterized in that the discharge vessel also comprises Ce halide.



1/2




FIG. 1




FIG. 2

2/2




FIG. 3

## INTERNATIONAL SEARCH REPORT

Intern. Application No

PCT/EP 00/00216

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 H01J61/82

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H01J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 98 25294 A (PHILIPS ELECTRONICS NV ;PHILIPS NORDEN AB (SE)) 11 June 1998 (1998-06-11) abstract; claims 1,2; figure 2 page 4, line 25 - line 28 page 7, line 12 - line 13 page 7, line 27 - line 34 ---	1-5
X	US 3 639 801 A (JACOBS CORNELIS ADRIANUS JOANN ET AL) 1 February 1972 (1972-02-01) abstract; claim 1 column 2, line 50 - line 52 column 3, line 7 - line 34 column 3, line 45 - line 58 column 4, line 5 - line 17 column 4, line 24 - line 52 --- -/--	1-4



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

## \* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

10 April 2000

Date of mailing of the international search report

26/04/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Martín Vicente, M

## INTERNATIONAL SEARCH REPORT

Interr. 1st Application No

PCT/EP 00/00216

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 161 672 A (CAP DANIEL M ET AL) 17 July 1979 (1979-07-17) abstract; claim 1; table 1 column 2, line 61 - column 3, line 10 column 8, line 45 - line 56 column 10, line 36 - line 40	1-4
X	US 5 525 863 A (KOWALCZYK LOU ET AL) 11 June 1996 (1996-06-11) column 7, line 40 - column 8, line 5	1,2,4
P,X	WO 99 28946 A (KONINKL PHILIPS ELECTRONICS NV ; PHILIPS AB (SE)) 10 June 1999 (1999-06-10) abstract; claims 1-3; figure 2 page 2, line 2 - line 24 page 3, line 4 - line 12 page 3, line 30 - line 31 page 4, line 13 - line 15 page 5, line 31 - page 6, line 4	1,2,4,5
A	WO 97 42650 A (PHILIPS ELECTRONICS NV ; PHILIPS NORDEN AB (SE)) 13 November 1997 (1997-11-13) cited in the application abstract; figure 2 page 1, line 8 - line 19 page 2, line 5 - line 21 page 2, line 34 - page 3, line 30 page 6, line 20 - line 23 page 7, line 6 - line 14	1
A	WO 98 49715 A (KONINKL PHILIPS ELECTRONICS NV ; PHILIPS AB (SE)) 5 November 1998 (1998-11-05) abstract; figure 2	1
A	EP 0 286 247 A (EMI PLC THORN) 12 October 1988 (1988-10-12) abstract column 1, line 1 - line 9 column 2, line 29 - line 32 column 2, line 39 - line 44 column 2, line 50 - line 53 column 3, line 49 - column 4, line 1 column 4, line 58 - column 5, line 11 column 9, line 20 - line 23	1-3
A	US 4 724 361 A (WADA SHIGEAKI ET AL) 9 February 1988 (1988-02-09) column 8, line 33 - line 36 column 9, line 19 - line 32 column 10, line 52 - column 11, line 22	1,4
	---	
	-/--	

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 00/00216

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 215 524 A (PHILIPS NV) 25 March 1987 (1987-03-25) abstract; claim 1 page 3, line 12 - line 19 page 5, line 4 - line 13 page 9, line 10 - page 10, line 3 page 13, line 4 - line 36 -----	1,3
A	EP 0 443 964 A (WELCH ALLYN INC) 28 August 1991 (1991-08-28) abstract; claim 18; figure 2 page 6, line 35 - line 43 page 6, line 54 - line 57 page 7, line 50 - line 53 -----	1,4
A	US 4 253 037 A (DRIESSEN ANTONIUS J G C ET AL) 24 February 1981 (1981-02-24) abstract; claim 4 column 3, line 34 - line 38 column 4, line 32 - line 40 column 4, line 64 - line 67 column 5, line 46 - line 50 column 6, line 27 - line 29 -----	1,2

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 00/00216

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9825294 A	11-06-1998	CN 1210619 A EP 0896733 A JP 2000501563 T PL 328092 A US 5973453 A	10-03-1999 17-02-1999 08-02-2000 04-01-1999 26-10-1999
US 3639801 A	01-02-1972	NL 6909891 A AT 297848 B BE 752550 A DE 2028781 A FR 2051304 A GB 1272545 A SE 355106 B	29-12-1970 15-03-1972 28-12-1970 07-01-1971 02-04-1971 03-05-1972 02-04-1973
US 4161672 A	17-07-1979	AU 505333 A BE 868764 A BR 7804360 A CA 1111483 A CH 635957 A DD 138925 A DE 2826733 A ES 471432 A FR 2397066 A GB 2000637 A, B IT 1096968 B JP 1452128 C JP 54063567 A JP 62053904 B JP 59103270 A MX 145363 A NL 7807285 A, B, SE 435333 B SE 7807546 A	15-11-1979 05-01-1979 03-04-1979 27-10-1981 29-04-1983 28-11-1979 18-01-1979 01-10-1979 02-02-1979 10-01-1979 26-08-1985 25-07-1988 22-05-1979 12-11-1987 14-06-1984 27-01-1982 09-01-1979 17-09-1984 06-01-1979
US 5525863 A	11-06-1996	DE 69323578 D DE 69323578 T EP 0581359 A JP 6162996 A	01-04-1999 19-08-1999 02-02-1994 10-06-1994
WO 9928946 A	10-06-1999	EP 0956582 A	17-11-1999
WO 9742650 A	13-11-1997	CA 2226556 A CN 1196826 A EP 0838081 A JP 11509679 T US 5923127 A	13-11-1997 21-10-1998 29-04-1998 24-08-1999 13-07-1999
WO 9849715 A	05-11-1998	EP 0910866 A JP 2000501564 T	28-04-1999 08-02-2000
EP 0286247 A	12-10-1988	AT 60166 T GR 3001547 T JP 63257179 A US 4910432 A	15-02-1991 23-11-1992 25-10-1988 20-03-1990
US 4724361 A	09-02-1988	JP 61165999 A DE 3543986 A FR 2574990 A	26-07-1986 26-06-1986 20-06-1986

## INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/EP 00/00216

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4724361 A		JP 1939774 C	09-06-1995
		JP 6065023 B	22-08-1994
		JP 62097251 A	06-05-1987
		GB 2169440 A, B	09-07-1986
		GB 2211658 A, B	05-07-1989
		JP 2076367 C	25-07-1996
		JP 6030244 B	20-04-1994
		JP 62090843 A	25-04-1987
EP 0215524 A	25-03-1987	NL 8502509 A	01-04-1987
		AT 45056 T	15-08-1989
		AU 6258586 A	19-03-1987
		BR 8604319 A	05-05-1987
		CA 1263138 A	21-11-1989
		CN 1008030 B	16-05-1990
		DD 249567 A	09-09-1987
		ES 2005822 A	01-04-1989
		FI 863659 A	14-03-1987
		HU 42203 A, B	29-06-1987
		JP 62066556 A	26-03-1987
EP 0443964 A	28-08-1991	US 5144201 A	01-09-1992
		AU 633178 B	21-01-1993
		AU 7095091 A	29-08-1991
		CA 2036901 A	24-08-1991
		CN 1058862 A	19-02-1992
		DE 69102791 D	18-08-1994
		DE 69102791 T	24-11-1994
		ES 2025500 A	16-03-1992
		JP 4218253 A	07-08-1992
		ZA 9101321 A	24-12-1991
US 4253037 A	24-02-1981	NL 7801972 A	24-08-1979
		AT 379709 B	25-02-1986
		AT 126779 A	15-06-1985
		AU 522231 B	20-05-1982
		AU 4433579 A	30-08-1979
		BE 874313 A	20-08-1979
		BR 7901043 A	02-10-1979
		CA 1118832 A	23-02-1982
		DE 2906383 A	23-08-1979
		ES 477871 A	16-12-1979
		FR 2418546 A	21-09-1979
		GB 2015243 A, B	05-09-1979
		HU 181472 B	28-07-1983
		IN 150128 A	31-07-1982
		IT 1111542 B	13-01-1986
		JP 1033900 B	17-07-1989
		JP 1555757 C	23-04-1990
		JP 54124574 A	27-09-1979



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

THIS PAGE BLANK (USPTO)

THIS PAGE BLANK (USPTO)